

Three Phase String Inverter

SUN-15K-G05-AU



2 MPP trackers, Max. efficiency up to 98.5%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)

Deye

Stock Code: 605117.SH

Model		SUN-15K-G05-AU
Input Side		
Max. DC Input Power (kW)		19.5
Max. DC Input Voltage (V)		1000
Min Input DC Operating Voltage Range (V)		200-1000
Start-up DC Input Voltage (V)		250
MPPT Operating Range (V)		200~850
Max. DC Input Current (A)		13+26
Max. Short Circuit Current (A)		19.5+39
Number of MPPT / Strings per MPPT		2/1+2
Output Side		
Rated Output Power (kW)		15
Rated Output Power (VA)		15
Max. Active Power (kW)		15
Nominal Output Voltage / Range (V)	3L/N/PE	380V/323V-418V, 400V/340V-440V
Rated Grid Frequency (Hz)		50 / 60 (Optional)
Operating Phase		Three phase
Rated AC Grid Output Current (A)		21.7
Max. AC Output Current (A)		21.7
Output Power Factor		0.8 leading to 0.8 lagging
Grid Current THD		<3%
DC Injection Current (mA)		<0.5%
Grid Frequency Range		47~52 or 57~62 (Optional)
Efficiency		
Max. Efficiency		98.5%
Euro Efficiency		97.5%
MPPT Efficiency		>99%
Protection		
DC Reverse-Polarity Protection		Yes
AC Short Circuit Protection		Yes
AC Output Overcurrent Protection		Yes
Output Overvoltage Protection		Yes
Insulation Resistance Protection		Yes
Ground Fault Monitoring		Yes
Anti-islanding Protection		Active Frequency Shift
Temperature Protection		Yes
Integrated DC Switch		Yes
Remote software upload		Yes
Remote change of operating parameters		Yes
Protective Class		Class I
Surge protection		DC Type II / AC Type II
Overvoltage Category		DC Type II / AC Type III
General Data		
Size (mm)		332W×472H×203D
Weight (kg)		15
Topology		Transformerless
Internal Consumption		<1W (Night)
Running Temperature		-25~65
Ingress Protection		IP65
Noise Emission (Typical)		≤ 40 dB
Cooling Concept		Natural cooling
Max. Operating Altitude Without Derating		4000m
Warranty		5 years
Grid Connection Standard		AS/NZS 4777.2
Operating Surroundings Humidity		0-100%
Safety EMC / Standard		IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2
Features		
DC Connection		VP-D4B
AC Connection		IP65 rated plug
Display		LCD1602
Interface		RS485/RS232/Wifi/LAN